



General Info	
Managers	Terminal Quequen S.A.
Location	Quequen River (Left margin)
Berth	Port side

Frontage (in meters)	110
Max. LOA (in meters)	230
Depth (in meters)	12,2
Air Draft at Datum (in meters)	14
Cargo Suitability	Grain, By products & Bulk Cargo



Port Facilities	Silo - Belt Conveyor
-----------------	----------------------

### Berth 6 - Quequén

Loading / Discharging rates	
Grain	abt 1600 Mt x Hour
By Products	abt 700 Mt x Hour

Cargoes Loaded
SBMP
SBM
SFMP

Working time	
Monday to Friday	From 0700 hs to 1900 hs
Saturday	Overtime
Shift	6 Hours
Remaining times are considered as overtime	

Fresh Water	Bunker / Slop operations
Available at this berth	Available (By Trucks)

Relevant Info	
Water Density	Brackish (Dens. 1015/1020)
Tides Difference	1,00 m / 1,20 m

Tug Boats	
LOA up to 80m	No need
LOA between 80 & 100 m	1 Tugboat
LOA over 140 m	2 Tugboats

Stowage Factors	
Barley	48,5/49,3
Wheat	44,5
SBS	48,7/48
SFP	59,2/59,6
SFMP (34/35 %)	60/61
SFMP (37/38 %)	56/57
SBMP (Lp)	51/52
SBMP (Hp)	48/49
SBM (42%)	56/57
SBM (44%)	55/56
SBM (48%)	53/54

[Go back to Menu](#)