



General Info	
Managers	Terfe S.A.* (Nidera Subsidiary)
Location	Quequen River (Right margin)
Berth	Starboard Side

Frontage (in meters)	210
Max. LOA (in meters)	230
Depth (in meters)	13,1
Air Draft at Datum (in meters)	N/A
Cargo Suitability	General Cargo, Bulk Cargo & Forestry products

Port Facilities	Open Storage
-----------------	--------------

Loading / Discharging rates	
Fertilizers (for disch.)	abt 3200 Mt daily (12 hours)

Working time	
Monday to Friday	From 0700 hs to 1900 hs
Saturday	Overtime
Shift	6 Hours
Remaining times are considered as overtime	

Fresh Water	Bunker / Slop operations
Available at this berth	Available (By Trucks)

Relevant Info	
Water Density	Brackish (Dens. 1015/1020)
Tides Difference	1,00 m / 1,20 m

Tug Boats	
LOA up to 80m	No need
LOA between 80 & 100 m	1 Tugboat
LOA over 140 m	2 Tugboats



Berths 9/10 - Necochea

- * Open quay
- * Discharge by vessel's cranes

Stowage Factors	
Barley	48,5/49,3
Wheat	44,5
SBS	48,7/48
SFP	59,2/59,6
SFMP (34/35 %)	60/61
SFMP (37/38 %)	56/57
SBMP (Lp)	51/52
SBMP (Hp)	48/49
SBM (42%)	56/57
SBM (44%)	55/56
SBM (48%)	53/54

* Terminal de Fertilizante S.A.